

LDV49-LAI200

49" Floor Standing LCD Digital Signage



Technical Specification

Specification

External Storage (SD)

Decoding Ability

Model	LDV49-LAI200	
Panel size	49"TFT-LCD	
Display ratio	16:9	
Maximum resolution	1920×1080	
Display color	16.7M	
Brightness (nits)	400cd/ m²	
Contrast	3500:1	
Viewing angle	178°/178°	
Backlight	LED	
Response Time	8ms	
Display Mode	Vertical	
Performance		
System	Android4.4.4	
RAM	2 GB	
Internal Storage	8G	

16G standard, expandable up to 64G

2CH@1080P@60fps

Features:

- · Industrial design, metal housing makes the device wearable and anti-magnetic, protective glass design and painting process make the device body smooth, dustproof and anti-crash
- \cdot Various play formats, support video, picture, text, audio and other multimedia information display, made for advertising industry
- \cdot Remote device management, support remote timing switch, adjust volume, synchronize the time of terminal, screen shot, remote upgrade
- · Various play modes, support cycle play, specified time play, inter-cut, interval play and so on
- \cdot Multi-level permission settings and management, unaudited programs can not be added to the schedule and play at the terminal













Built in Loudspeaker	8Ω/5W×2
Uplink Network	Ethernet port, Wi-Fi, 3G/4G(optional)
Interface	
USB	USB2.0×2
SD	1
RJ45	1
Wi-Fi	1
Audio Output	HDMI×1, Audio×1
SIM	1(optional, for 3G/4G module)
Others	
Dimension	1901.0×696.4×72.6mm
Package Size	2060.0×880.0×255.0mm
Net Weight	67kg
Installation Mode	Floor Standing
Power	AC100~240V, 50Hz/60Hz
Standard Consumption	120W
Standby Consumption	≤0.5W

LDV49-LAI200



Work Environmet	Temperature: 0 °C~+60 °C
Work Environmet	Humidity: 10%~80%
Change Facility and the	Temperature: -20°C~+60°C
Storage Environmet	Humidity: 10%~85%
Ingress Protection	IPX5